

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable	Conditions To Avoid NONE KNOWN
Incompatibility (Materials to Avoid)	NONE KNOWN
Hazardous Decomposition Products	RESPIRABLE DUST PARTICLES MAY BE GENERATED BY HANDLING
HAZARDOUS POLYMERIZATION <input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	Conditions To Avoid NA

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY	<input checked="" type="checkbox"/> Inhalation <input type="checkbox"/> Skin Absorption	<input type="checkbox"/> Ingestion <input type="checkbox"/> Not Hazardous	CARCINOGEN LISTED IN	<input type="checkbox"/> NTP <input type="checkbox"/> IARC Monograph	<input type="checkbox"/> OSHA <input checked="" type="checkbox"/> Not Listed	
HEALTH HAZARDS	Acute	IRRITATION OF EYES, THROAT AND NASAL PASSAGES				
	Chronic	AIRBORNE RESPIRABLE DUST CONTAINING QUARTZ CAN RESULT IN SILICOSIS				
Signs and Symptoms of Exposure	ILV: AIRBORNE NUISANCE DUST: TOTAL = 10mg/m ³ , RESPIRABLE = 5mg/m ³					
Medical Conditions Generally Aggravated by Exposure	IRRITATION OF EYES THROAT AND NASAL PASSAGES					
EMERGENCY FIRST AID PROCEDURES - Seek medical assistance for further treatment, observation and support if necessary.						
Eye Contact	FLUSH EYES WITH RUNNING WATER FOR 15 MINUTES.					
Skin Contact	WASH WITH SOAP AND WATER.					
Inhalation	REMOVE TO FRESH AIR, DUST IN THROAT AND NASAL PASSAGES SHOULD CLEAR SPONTANEOUSLY.					
Ingestion	SEEK MEDICAL ADVICE.					

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type)	NIOSH - MSHA APPROVED DUST RESPIRATORS FOR CONDITIONS EXCEEDING TLV.				
Protective Gloves	NA	Eye Protection	SAFETY GLASSES		
VENTILATION TO BE USED	<input checked="" type="checkbox"/> Local Exhaust	<input type="checkbox"/> Mechanical (general)	<input type="checkbox"/> Special		
	<input type="checkbox"/> Other (specify):				
Other Protective Clothing and Equipment	NOT NEEDED				
Hygienic Work Practices	WASH WORK CLOTHING AFTER EACH USE.				

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

Steps to be Taken if Material Is Spilled Or Released	WET MATERIAL DOWN TO PREVENT DUST EXPOSURE AND/OR USE PROTECTIVE RESPIRATORY EQUIPMENT.				
Waste Disposal Methods	ALLOW TO DRY AND RE-USE.				
Precautions to be Taken in Handling and Storage	RESPIRABLE DUST LEVELS SHOULD BE MONITORED.				
Other Precautions and/or Special Hazards	CHRONIC EXPOSURE TO RESPIRABLE LIMESTONE DUST IN EXCESS OF APPROPRIATE EXPOSURE LIMITS CAN CAUSE PNEUMOCONIOSIS (LUNG DISEASE).				

NFPA Rating* Health ___ Flammability ___ Reactivity ___ Special ___ | HMIS Rating* Health ___ Flammability ___ Reactivity ___ Personal Protection ___